

PGE UPS 1050+



Power Backup + Protection

Give Protection from Power impurities.
Save your work & equipment when

- Upto 60 minutes backup on a single PC
- Line interactive design
- High efficiency microprocessor based design
- AVR input voltage range 140V- 290VAC
- Dual 9AH heavy duty battery inside
- Boost and buck AVR (Auto voltage regulation)
- Cold start function (DC Power ON)
- Short circuit and overload protection
- Advanced battery management (ABM technology)
- Automatically charging when UPS OFF
- Sleek, compact & small footprint cabinet

Model	PGE1050 +	
Capacity	1000VA/600W	
Input	Voltage	230V
	Frequency Range	45-55Hz
	AVR	145V-275V
	Connection (1.5m wire)	3 pin 6A, Indian plug
Output	Voltage on mains	230V + 10% -15%
	Frequency on mains	Follows input
	Voltage on Battery	230V ± 5%
	Waveform	Quasi sinewave
	Power Factor Lagging	0.6
	Efficiency	> 80%
	Sockets	3 x universal sockets
Protection	Input Protection	Fuse
	O/P short circuit	UPS shutdown immediately
	O/P overload shutdown	110% for 3 min, 150% for 10 Sec
Transfer Time	Mains to Inverter	4 - 8 ms
Battery	DC Bus	24V
	Internal Battery	2 x 9 AH, SMF
	Life	2-3 years typical lifetime
	External Battery	Nil
	Protection	Auto discharge protection
	Typical Recharging time	8 (to 90% full capacity)
	Backup Time	40-50 mins on 1 PC load
Indications	Power ON	Green LED
	Inverter ON	Red LED
	Battery charging	Yellow LED
Alarm	Battery backup	Slow beeping sound (about 0.47Hz)
	Battery Low	Rapid beeping sound (about 1.8 Hz)
	Overload	Continuos beeping sound
Environment	Ambient operation	0-40°C, 0-95% humidity non condensing, 3500 meter max.
	Audible noise	< 40 DbA (1 meter from surface)
	Storage Condition	15,000 meter max. Elevation
Physical	Weight	12 Kgs.
	Dimension - DxWxH (mm)	430x210x240

Specification subject to change without prior intimation



UPS with Built in Battery - Plug & Play - 1 year warranty